



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 140, DN 63 (ID 2½'')
Ordering No. 14036-CE08

Description

Flange	CF-F 63
Actuator	Manual, handwheel – With position indicator
Feedthrough	Rotary feedthrough

Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 2 bar (abs)
Differential pressure on the gate		≤ 2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		440 ls ⁻¹
Cycles until first service	– Unheated and under clean conditions	200 000
Temperature	– Valve body	≤ 150 °C
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	≤ 80 °C
	– Position indicator	≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	– Valve body	AISI 304 (1.4301)
	– Mechanism	AISI 304 (1.4301), AISI 301 (1.4310)
Seal	– Bonnet	FKM (Viton®), Vulcanized
	– Gate	FKM (Viton®), O-ring
	– Actuator	FKM (Viton®), NBR
Mounting position		any
Weight		11 kg / 25 lbs

Created by: JOM	Release date: 2017-04-05	1 of 2
Modified by:	Release date:	889536EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 140, DN 63 (ID 2½")

Ordering No. 14036-CE08

Position indicator

Type


Micro switch

Voltage

≤ 250 V AC ≤ 50 V DC

Current max.

≤ 5 A ≤ 3 A



Wiring diagram

Created by: JOM	Release date: 2017-04-05	2 of 2
Modified by:	Release date:	889536EA